

KS8309

Smart Dynamic QR Terminal



Food & Beverage



Fashion & Retail

QR Terminal



Powered by
RTOS

Cloud
Based

2.4"
Display



















Long
Standby

Advanced
Connecticut

KS8309

Mobile QR Payment

SPECIFICATIONS

	Operating system	RTOS (MQTT Communication Service)
	Processor	ARM Cortex-R5 614MHz
	Memorial	16MB RAM + 8MB ROM;
	Card Reads	NO
	Cameras	NO
	Display	Front: 2.4 inches 240*320 LCD with backlight control Rear: 6-digit digital display, black and white mode
	Comms	4G LTE-TDD Wi-Fi NFC tap by phone (optional)
	Battery	2000mAh 3.7V (optional 2700mAh 3.7V)
	Printer	NO
	SIM / SAM	1 Mini SIM
	Positing	NO
	Key/Buttons	5 Keys: Power On/OFF Volume + Volume - Function Reset
	Audio	110db Speaker 3W 4Ω
	Ports	1 Type-C USB (OTG)
	Physical	Terminal only: 160X115X70.4mm, 262g (including battery) Terminals with package: 170 X 80 X 120mm, 290g.
	Environmental	0 °C ~ 50 °C (32 °F ~ 122 °F) Operating Temperature -20 °C ~ 70 °C (-4 °F ~ 158 °F) Storage Temperature 10% ~ 90% Relative Humidity, No-Condensing
	Accessories	Charging Cable Micro-USB
	Certifications	CE RoHS CCC

